



100% WOOD



POSSIBILITY OF PAINTING



HIGH SCRATCHES AND DIRT RESISTANCE



EASY ASSEMBLY WITH CLIPS




DUCTS FOR CABLES



HIGH MOISTURE RESISTANCE

TECHNICAL SPECIFICATION FOR P6P FOILED SKIRTING BOARD




MATERIAL/ APPEARANCE

Skirting boards made of 100% wood, covered with finish-type foil on the outside.

Skirting board cross-section:

1. Finish white foil veneer.
2. Knot-free softwood core (pine).
3. Place for mounting clips.
4. Cable cutout..



APPLICATION

Wooden skirting boards from Barlinek they are made entirely of natural softwood, finger-jointed, which guarantees them extraordinary durability. The decorative surface and the edges of the white foiled strips are covered in one piece along the length of the strip with white finish foil. Such a strip does not require additional protection or painting.



100% WOOD



POSSIBILITY OF PAINTING



HIGH SCRATCHES AND CHIP RESISTANCE



EASY ASSEMBLY WITH CLIPS





DUCTS FOR CABLES



HIGH MOISTURE RESISTANCE

COLOUR OF THE SURFACE LAYER

Index/EAN code/ catalogue number	Illustrative photo of the color of the skirting board*	Index/EAN code/catalogue number	Illustrative photo of the color of the skirting board*
Index: LIS-BIA-FO2-220-060-P6P Catalogue no: P6P18101A EAN code: 5906737984970		Index: LIS-CZA-FO2-220-060-P6P Catalogue no: P6P28101A EAN code: 5906737990902	

CHARACTERISTICS/ INSTALLATIONS

The humidity of the skirting board:	9% +/-2%
Assembly:	We recommend the use of "Barclips" mounting clip. A detailed mounting instructions of skirting boards can be found on www.Barlinek.com and in the mounting instructions of Barlinek's floorboards.
Intended use:	Rooms inside buildings with a relative air humidity of 45% to 60%
Permissible bend deflection of a skirting board:	22 mm/ 2200mm of the length
Blue stain of pine wood	Permissible, up to 50% of the wood surface

THE DIMENSIONS OF AN INDIVIDUAL ELEMENT

Length:	2200mm Due to the lack of impact of this parameter on the mounting: Applicable tolerances are the following: <ul style="list-style-type: none"> one skirting board in a package can have a +/- 10mm length variation two skirting boards in a package can have a +/-5mm length variation
Width:	15,5mm (+/-0.5mm)
Height:	60mm (+/-0.5mm)

PACKAGE / WEIGHT

The weight of one skirting board	0,946 kg
The number of skirting boards in the package:	10pcs. = 22m
The weight of one package:	9,66 kg
Number of packages per pallet:	78 packages.
Pallet weight (skirting boards + a pallet):	775,68 kg
The dimensions of one pallet (H/W/L)	1320mm x 830mm x 2200mm

***NOTE:** Sample skirtings boards, samples, photo- graphs and merchandising brochures may not fully correspond to the actual appearance of the products. The color of the product delivered may be different from the material available at the point of sale.